

Material Safety Data Sheet

EU Regulation: 2020/878

SECTION 1: IDENTIFICATION OF	THE SUBSTANCE	/MIXTURE /	AND OF THE COMPA	NY/UNDERTAKING		
1.1 Product Identification						
Product Name	Ylang Ylang 3, E	ssential Oil				
BIOLOGICAL DEFINITION		CANANGA ODORATA FLOWER OIL IS THE THIRD STAGE FRACTION OBTAINED BY THE DISTILLATION OF YLANG YLANG FLOWERS, CANANGA ODORATA, ANONACEAE.				
INCI NAME	CANANGA ODORAT	ta Flower O	IL			
Synonyms & Trade Names	-					
INTERNAL PRODUCT CODE	K0498					
CAS-No	83863-30-3 / 8006-81-3 / 68606-83-7	EC No.	281-092-1	EINECS No.	281-092-1	
1.2 DETAILS OF THE SUPPLIER OF THE SAFETY DAT	A SHEET					
COMPANY ADDRESS	O&3 Unit 2, Athelstan Bu	usiness Park, H	lanwell Lane, Hutton Cor	nyers, Ripon, HG4 5BF,	England.	
EMAIL	TECHNICALCREW@O	and 3. com				
1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DAT	A SHEET					
EMERGENCY CONTACTS	(07968 200167)					





SECTION 2: HAZARDS IDENTIFICATION	
2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE	THE FULL TEXT FOR ALL HAZARD STATEMENTS IS DISPLAYED IN SECTION 16.
CLASSIFICATION (EU1272/2008)	Physical hazards: Not classified Health hazards: Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Asp. Tox. 1 - H304 Environmental hazards: Aquatic Chronic 2 - H411
2.2 LABEL ELEMENTS	Label in accordance with Regulation (EC) No 1272/2008.
GHS LABEL	GHS07 GHS08 GHS09
Signal Word	Danger
Contains	Beta Caryophyllene, Benzyl Salicylate, Linalool, Geranyl Acetate, Farnseol, Isoeugenol
HAZARDS STATEMENT	H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
Precautionary Statements	P261 Avoid breathing vapour/spray. P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of water. P331 Do NOT induce vomiting. P501 Dispose of contents/ container in accordance with national regulations.
SUPPLEMENTARY PRECAUTIONARY STATEMENTS	P272 CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE. P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION. P321 SPECIFIC TREATMENT (SEE MEDICAL ADVICE ON THIS LABEL). P332+P313 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ ATTENTION. P333+P313 IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ ATTENTION. P362+P364 TAKE OFF CONTAMINATED CLOTHING AND WASH IT BEFORE REUSE. P391 COLLECT SPILLAGE. P405 STORE LOCKED UP.
2.3	SECTION 16 (OTHER INFORMATION): RISK & SAFETY PHRASES IN FULL.
OTHER HAZARDS ADVERSE PHYSIO-CHEMICAL PROPERTIES	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION.
ADVERSE EFFECTS ON HUMAN HEALTH	Toxic to aquatic life with long lasting effects.
PBT or vPvB according to Annex XIII	NO ADDITIONAL DATA AVAILABLE.
	I
SECTION 3: COMPOSITION OF INGREDIEN	ITS
3.1 Substances	10-15% Beta Caryophyllene CAS No: 7-44-5 EC No: 201-746-1 Classification (EC 1272/2008): M factor (Acute) = 1 M factor (Chronic) = 1 M factor (Chronic) = 1 Skin Irrit. 2 - H315, Skin Sens. 1B - H317, Asp. Tox. 1 - H304, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410 5-10% Benzyl Benzoate CAS No: 120-51-4 EC No: 204-402-9 Classification (EC 1272/2008): M factor (Acute) = 1 Acute Tox. 4 - H302, Aquatic Acute 1 - H400, Aquatic Chronic 2 - H411
	5 - 10% BENZYL SALICYLATE CAS NO: 118-58-1 EC NO: 204-262-9 CLASSIFICATION (EC 1272/2008): EYE IRRIT. 2 - H319, SKIN SENS. 1B - H317, AQUATIC CHRONIC 3 - H412





•	CLASSIFICATION (EC 1272/2008):	78-70-6 EC No: 201-134-4 Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, Skin Sens. 1 - H317 CAS No: 140-11-4 EC No: 205-399-7
		AQUATIC CHRONIC 3 - H412
		CAS No: 105-87-3 EC No: 203-341-5 Rit. 2 - H315, Skin Sens. 1B - H317, Aquatic Chronic 3 -
	1 - 5% Farnseol CAS No: 4602-84 Classification (EC 1272/2008): Skin Irrit. 2 - H315, Skin Sens. 1 - H317,	M FACTOR (ACUTE) = 1 M FACTOR (CHRONIC) = 1
		CAS No: 104-93-8 EC No: 203-253-7 Acute Tox. 4 - H302, Skin Irrit. 2 - H315, Repr. 2 - H361
		CAS No: 97-54-1 EC No: 202-590-7 Fox. 4 - H302, Acute Tox. 4 - H312, Skin Irrit. 2 - H315, STOT SE 3 - H335
	≤ 1.0% Geraniol CAS No: 106-24- Classification (EC 1272/2008):	1 EC No: 203-377-1 Skin Irrit. 2 - H315, Eye Dam. 1 - H318, Skin Sens. 1 - H317
	≤ 1.0% EUGENOL CAS NO: CLASSIFICATION (EC 1272/2008):	97-53-0 EC No: 202-589-1 Eye Irrit. 2 - H319, Skin Sens. 1 - H317, Asp. Tox. 1 - H304

SECTION 4: FIRST AID MEASURES	
4.1 Description of First Aid Measures	
GENERAL INFORMATION	ALWAYS REMOVE CONTAMINATED CLOTHING IMMEDIATELY.
INHALATION	GET MEDICAL ATTENTION IMMEDIATELY. REMOVE FROM EXPOSURE SITE TO FRESH AIR, KEEP AT REST, AND OBTAIN MEDICAL ATTENTION.
INGESTION	DO NOT INDUCE VOMITING. IMMEDIATELY RINSE MOUTH AND PROVIDE FRESH AIR. GET MEDICAL ADVICE/ATTENTION.
Skin Contact	REMOVE CONTAMINATED CLOTHES. WASH THOROUGHLY WITH SOAP AND WATER. CONTACT PHYSICIAN IF IRRITATION PERSISTS.
Eye Contact	IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR UP TO 15 MINUTES. REMOVE ANY CONTACT LENSES AND OPEN EYES WIDE APART. GET MEDICAL ADVICE/ATTENTION. CONTINUE TO RINSE.
4.2 MOST IMPORTANT SYMPTOMS & EFFECTS (ACUTE & DELAYED)	No additional Data Available.
4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION OR SPECIAL TREATMENT REQUIRED	TREAT SYMPTOMATICALLY.





SECTION 5: FIRE FIGHTING MEASURES 5.1 SUITABLE EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM. **EXTINGUISHING MATERIAL** UNSUITABLE EXTINGUISHING MEDIA: DO NOT USE WATER JET AS AN EXTINGUISHER, AS THIS MAY SCATTER AND SPREAD FIRE. A FIRE WILL OFTEN PRODUCE A THICK BLACK SMOKE, EXPOSURE TO DECOMPOSITION PRODUCTS MAY BE HAZARDOUS TO 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR HEALTH. DO NOT BREATHE IN SMOKE. MIXTURE THERMAL DECOMPOSITION OR COMBUSTION PRODUCTS MAY INCLUDE THE FOLLOWING SUBSTANCES: CARBON DIOXIDE (CO2), CARBON MONOXIDE (CO), OTHER TOXIC GASES. CONTAINERS CLOSE TO FIRE SHOULD BE REMOVED OR COOLED WITH WATER. 5.3 AVOID INHALATION OF GENERATED FUMES OR VAPOURS. WEAR SELF-CONTAINED BREATHING APPARATUS AND APPROPRIATE **ADVICE FOR FIRE-FIGHTERS** PROTECTIVE CLOTHING.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Handle the product using protective gloves resistant to the chemicals exposed. Avoid contact with skin and inhalation of its vapours. Maintain adequate ventilation in the working area after spilling.
6.2	Do not discharge into drains, water courses or onto the ground. Dispose of in line with Local authority
ENVIRONMENTAL PRECAUTIONS	GUIDELINES.
6.3 METHODS & MATERIAL FOR CONTAINMENT AND CLEANING UP	REMOVE IGNITION SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE INHALATION OF VAPOURS. CONTAIN SPILLAGE IMMEDIATELY BY USE OF SAND OR INERT POWDER. DISPOSE OF ACCORDING TO LOCAL REGULATIONS.
6.4 References to other sections	REFER & CONSIDER SECTION 7, 8. REFER & CONSIDER SECTION 13.

SECTION 7: HANDLING & STORAGE

7.1 Precautions for safe-handling	HANDLE IN ACCORDANCE WITH GOOD HYGIENE AND SAFETY PRACTICE. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES AND HOT SURFACES NO SMOKING. USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED. USE IN ACCORDANCE WITH GOOD MANUFACTURING AND INDUSTRIAL HYGIENE PRACTICES. USE IN AREAS WITH ADEQUATE VENTILATION DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP THE PRODUCT CONTAINER TIGHTLY CLOSED, IN A DRY, VENTILATED AREA. KEEP AWAY FROM POTENTIAL SOURCES OF IGNITION AND PROTECTED FROM LIGHT. MAINTAIN LIMITED CONTACT WITH OXYGEN.
7.3 Specific end use(s)	No Data.

SECTION 8: EXPOSURE CONTROLS & PERSONAL PROTECTION

PERSONAL PROTECTION BENZYL SALICYLATE (CAS: 118-58-1) DNEL WORKERS - INHALATION; LONG TERM SYSTEMIC EFFECTS: 3.17 MG/M³ WORKERS - DERMAL: LONG TERM SYSTEMIC EFFECTS: 0.9 BW/DAY, MG/KG GENERAL POPULATION - INHALATION; LONG TERM SYSTEMIC EFFECTS: 0.78 MG/M³ GENERAL POPULATION - DERMAL; LONG TERM SYSTEMIC EFFECTS: 0.45 BW/DAY, MG/KG GENERAL POPULATION - ORAL; LONG TERM SYSTEMIC EFFECTS: 0.45 MG/KG, BW/DAY PNFC 8.1 - FRESH WATER; SHORT TERM 0.001 MG/L **CONTROL PARAMETERS** INTERMITTENT RELEASE, 0.01 MG/L - FRESH WATER; SHORT TERM 0 MG/L - MARINE WATER; - STP: SHORT TERM 10 MG/L - SEDIMENT (FRESHWATER); SHORT TERM 0.583 MG/KG - SEDIMENT (MARINE WATER); SHORT TERM 0.058 MG/KG - SOIL: SHORT TERM 1.41 MG/KG





LINALOOL (CAS: 78-70-6)

LINALOOL (CAS: 78-70-6)	
DNEL	
WORKERS - DERMAL;	SHORT TERM SYSTEMIC EFFECTS: 5 MG/KG
WORKERS - INHALATION; WORKERS - DERMAL;	SHORT TERM SYSTEMIC EFFECTS: 16.5 MG/M ³
WORKERS - INHALATION;	Long term systemic effects: 2.5 mg/kg Long term systemic effects: 2.8 mg/m ³
GENERAL POPULATION - ORAL;	SHORT TERM SYSTEMIC EFFECTS: 2.0 MG/M ⁻
GENERAL POPULATION - DERMAL;	SHORT TERM SYSTEMIC EFFECTS: 2.5 MG/KG
GENERAL POPULATION - INHALATION; SHORT	
GENERAL POPULATION - ORAL;	LONG TERM SYSTEMIC EFFECTS: 0.2 MG/KG
GENERAL POPULATION - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 1.25 MG/KG
GENERAL POPULATION - INHALATION;	LONG TERM SYSTEMIC EFFECTS: 0.7 MG/M ³
PNEC	
- STP;	SHORT TERM 10 MG/L
- Soil;	SHORT TERM 0.327 MG/KG
- INTERMITTENT RELEASE;	SHORT TERM 2 MG/L
- FRESH WATER;	SHORT TERM 0.2 MG/L
- MARINE WATER;	SHORT TERM 0.02 MG/L
- SEDIMENT (FRESHWATER);	SHORT TERM 2.22 Mg/Kg
- SEDIMENT (MARINE WATER);	SHORT TERM 0.222 MG/KG
GERANYL ACETATE (CAS: 105-87-3)	
DNEL	
WORKERS - INHALATION;	LONG TERM SYSTEMIC EFFECTS: 62.59 MG/M ³
WORKERS - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 35.5 BW/DAY, MG/KG
GENERAL POPULATION - INHALATION; LONG	
GENERAL POPULATION - DERMAL; GENERAL POPULATION - ORAL;	LONG TERM SYSTEMIC EFFECTS: 17.75 MG/KG, BW/DAY
GENERAL POPULATION - ORAL; PNEC	LONG TERM SYSTEMIC EFFECTS: 8.9 MG/KG, BW/DAY
- FRESH WATER;	SHORT TERM 3.72 MG/L
- FRESH WATER,	INTERMITTENT RELEASE; 37.2 MG/L
- MARINE WATER;	SHORT TERM 0.372 MG/L
- STP;	SHORT TERM 8 MG/L
- SEDIMENT (FRESHWATER);	SHORT TERM 0.442 MG/KG
- SEDIMENT (MARINE WATER);	SHORT TERM 0.044 MG/KG
- SOIL;	SHORT TERM 0.086 MG/KG
	,
BENZYL ACETATE (CAS: 140-11-4)	
DNEL	
WORKERS - INHALATION;	LONG TERM SYSTEMIC EFFECTS: 21.9 MG/M ³
WORKERS - INHALATION;	SHORT TERM SYSTEMIC EFFECTS: 43.8 MG/M ³
WORKERS - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 6.25 MG/KG, BW/DAY
WORKERS - DERMAL;	SHORT TERM SYSTEMIC EFFECTS: 12.5 BW/DAY, MG/KG
GENERAL POPULATION - INHALATION; LONG	
GENERAL POPULATION - INHALATION; SHORT	
GENERAL POPULATION - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 3.125 BW/DAY, MG/KG
GENERAL POPULATION - DERMAL;	SHORT TERM SYSTEMIC EFFECTS: 6.25 BW/DAY, MG/KG
GENERAL POPULATION - ORAL;	LONG TERM SYSTEMIC EFFECTS: 3.125 MG/KG, BW/DAY
GENERAL POPULATION - ORAL;	SHORT TERM SYSTEMIC EFFECTS: 6.25 MG/KG, BW/DAY
PNEC	
- FRESH WATER;	SHORT TERM 0.004 MG/L
- INTERMITTENT RELEASE,	FRESH WATER; 0.04 MG/L
- MARINE WATER;	Short term 0 mg/l
- STP;	SHORT TERM 8.55 MG/L
- SEDIMENT (FRESHWATER);	SHORT TERM 0.114 MG/KG
- SEDIMENT (MARINE WATER);	Short term 0.011 mg/kg
- Soil;	Short term 0.021 mg/kg
D_CDECVI METUVI ETUED /CAC. 104 02 01	
P-CRESYL METHYL ETHER (CAS: 104-93-8) DNEL	
WORKERS - INHALATION;	Long term systemic effects: 2.9 mg/m^3
WORKERS - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 2.7 MG/M ²
GENERAL POPULATION - INHALATION; LONG	
GENERAL POPULATION - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 8.3 BW/DAY, MG/KG
GENERAL POPULATION - DERMAL; GENERAL POPULATION - ORAL;	LONG TERM SYSTEMIC EFFECTS: 8.3 BW/DAY, MG/KG LONG TERM SYSTEMIC EFFECTS: 0.4 BW/DAY, MG/KG
GENERAL POPULATION - DERMAL; GENERAL POPULATION - ORAL; PNEC	LONG TERM SYSTEMIC EFFECTS: 0.4 BW/DAY, MG/KG
GENERAL POPULATION - DERMAL; GENERAL POPULATION - ORAL; PNEC - FRESH WATER;	LONG TERM SYSTEMIC EFFECTS: 0.4 BW/DAY, MG/KG SHORT TERM 0.027 MG/L
GENERAL POPULATION - DERMAL; GENERAL POPULATION - ORAL; PNEC	LONG TERM SYSTEMIC EFFECTS: 0.4 BW/DAY, MG/KG



	- SEDIMENT (MARINE WATER);	Short term 0.086 mg/kg
	GERANIOL (CAS: 106-24-1) DNEL	
	Workers - Inhalation;	LONG TERM SYSTEMIC EFFECTS: 161.6 mg/m^3
	WORKERS - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 12.5 MG/KG, BW/DAY
	GENERAL POPULATION - INHALATION;	LONG TERM SYSTEMIC EFFECTS: 47.8 MG/M ³
	GENERAL POPULATION - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 7.5 BW/DAY, MG/KG
	GENERAL POPULATION - ORAL; PNEC	LONG TERM SYSTEMIC EFFECTS: 13.75 BW/DAY, MG/KG
	- FRESH WATER;	SHORT TERM 0.011 MG/L
	- FRESH WATER;	INTERMITTENT RELEASE, 0.108 MG/L
	- MARINE WATER;	SHORT TERM 0.001 MG/L
	- STP;	SHORT TERM 0.7 MG/L
	- SEDIMENT (FRESHWATER);	SHORT TERM 0.115 MG/KG
	- SEDIMENT (MARINE WATER);	SHORT TERM 0.011 MG/KG
	- SOIL;	SHORT TERM 0.017 MG/KG
	EUGENOL (CAS: 97-53-0) DNEL	
	WORKERS - INHALATION;	LONG TERM SYSTEMIC EFFECTS: 21.2 mg/m^3
	WORKERS - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 6 BW/DAY, MG/KG
	GENERAL POPULATION - INHALATION; LONG TE	RM SYSTEMIC EFFECTS: 5.22 MG/M ³
	GENERAL POPULATION - DERMAL;	LONG TERM SYSTEMIC EFFECTS: 3 BW/DAY, MG/KG
	GENERAL POPULATION - ORAL; PNEC	LONG TERM SYSTEMIC EFFECTS: 3 BW/DAY, MG/KG
	- Fresh water;	SHORT TERM 1.13 MG/L
	- Fresh water;	INTERMITTENT RELEASE, 11.3 MG/L
	- MARINE WATER;	SHORT TERM 0.113 MG/L
	- SEDIMENT (FRESHWATER);	SHORT TERM 0.081 MG/KG
	- SEDIMENT (MARINE WATER);	SHORT TERM 0.008 MG/KG
	- Soil;	
8.2 EXPOSURE CONTROLS		

EYE PROTECTION	WEAR PROTECTIVE GLOVES/EYE PROTECTION/FACE PROTECTION.
HAND PROTECTION	WEAR PROTECTIVE GLOVES/EYE PROTECTION/FACE PROTECTION.
RESPIRATORY EQUIPMENT	UNDER NORMAL CONDITIONS OF USE AND WHERE ADEQUATE VENTILATION IS AVAILABLE TO PREVENT BUILD UP OF EXCESSIVE VAPOUR, THIS MATERIAL SHOULD NOT REQUIRE SPECIAL ENGINEERING CONTROLS. HOWEVER, IN CONDITIONS OF HIGH OR PROLONGED USE, OR HIGH TEMPERATURE OR OTHER CONDITIONS WHICH INCREASE EXPOSURE, THE FOLLOWING ENGINEERING CONTROLS CAN BE USED TO MINIMISE EXPOSURE TO PERSONNEL: A) INCREASE VENTILATION OF THE AREA WITH LOCAL EXHAUST VENTILATION. B) PERSONNEL CAN USE AN APPROVED, APPROPRIATELY FITTED RESPIRATOR WITH ORGANIC VAPOUR CARTRIDGE OR CANISTERS AND PARTICULATE FILTERS. C) USE CLOSED SYSTEMS FOR TRANSFERRING AND PROCESSING THIS MATERIAL. ALSO REFER TO SECTIONS 2 AND 7.
Hygiene Measures	GOOD PERSONAL HYGIENE PRACTICES ARE ALWAYS ADVISABLE, ESPECIALLY WHEN WORKING WITH CHEMICALS / OILS. DO NOT EAT, DRINK OR SMOKE DURING USE. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USING.
ENGINEERING MEASURES	PROVIDE ADEQUATE VENTILATION.
Skin Protection	WEAR PROTECTIVE CLOTHING TO REDUCE THE RISK OF SKIN AND EYE CONTACT.
PERSONAL PROTECTION	AVOID INHALATION OF THE PRODUCT. AVOID CONTACT WITH SKIN AND EYES.
Other Protection	WEAR SUITABLE PROTECTION TO AVOID CONTACT WITH SKIN AND EYES. DO NOT INHALE VAPOURS.
PROCESS CONDITIONS	ENSURE AREA IS WELL VENTILATED. AVOID VAPOUR INHALATION. SAFETY SHOWER & EYE BATH.
ENVIROMENTAL EXPOSURE CONTROLS	Avoid discharging into drainage water. Only eliminate by authorised companies.





SECTION 9: PHYSICAL & CHEMICAL PROPERTIES		
9.1 PHYSICAL & CHEMICAL PROPERTIES		
Appearance	Liquid	
COLOUR	PALE YELLOW – DARK YELLOW.	
Odour	CHARACTERISTIC.	
RELATIVE DENSITY	Approx 0.929 @ 20°C	
FLASH POINT (°C)	>88°C	
R EFRACTIVE INDEX @ 20 °C	Approx. 1.505 @ 20°C	
Solubility in water @ 20 $^\circ$ C	0.013G/LM WATER @25°C	
	Melting Point (°C): 15.76	
9.2	BOILING POINT (°C): 125	
OTHER INFORMATION	VAPOUR PRESSURE: 3.04 PA @25°C	
	AUTO-IGNITION TEMPERATURE (°C): 240.0	
9.2.1 INFORMATION WITH REGARD TO PHYSICAL HAZARD CLASSES	NO DATA.	
9.2.2 Other safety characteristics	No Data.	
SECTION 10: STABILITY & REACTIVITY		
10.1	PRESENTS NO SIGNIFICANT REACTIVITY HAZARDS, BY ITSELF OR IN CONTACT WITH WATER. STABLE UNDER NORMAL	
REACTIVITY	TEMPERATURE AND STORAGE CONDITIONS AND RECOMMENDED USE.	
10.2 Chemical stability	Stable under suggested storage conditions (<15°C).	
10.3 Possibility of hazardous reactions	NOT EXPECTED UNDER NORMAL CONDITIONS OF USE.	
10.4 Conditions to avoid	AVOID HEAT, FLAMES AND OTHER SOURCES OF IGNITION.	
10.5 Avoid contact with strong acids, alkalis or oxidising agents.		
10 /	NOT EXPECTED UNDER NORMAL TEMPERATURE CONDITIONS AND RECOMMENDED USE.	
10.6 HAZARDOUS DECOMPOSITION PRODUCTS	THERMAL DECOMPOSITION MAY RELEASE/FORM OXIDES OF CARBON (CARBON MONOXIDE, CARBON DIOXIDE) AND OTHER	
	TOXIC GASES.	

SECTION 11: TOXICOLOGICAL INFORMATION		
11.1 Toxicological effects		
Αсυτε Τοχιςιτγ	ATE ORAL (MG/KG) 6,410.26	
SKIN IRRITATION	MAY CAUSE SKIN IRRITATION.	
EYE DAMAGE OR IRRITATION	NOT CLASSIFIED	
R ESPIRATORY OR SKIN SENSITIVITY	SKIN - MAY CAUSE AN ALLERGIC SKIN REACTION.	
GERM CELL MUTAGENICITY	Not classified	
Carcinogenicity	NOT CLASSIFIED.	





R EPRODUCTIVE TOXICITY	NOT CLASSIFIED.
STOT – SINGLE EXPOSURE	NOT CLASSIFIED.
STOT – REPEATED EXPOSURE	NOT CLASSIFIED.
Aspiration Hazard	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
11.2 Information on other hazards	ΝΟ ΒΑΤΑ.
SECTION 12: ECOLOGICAL INFORMATION	
12.1 Τοχιατγ	Acute toxicity - Aquatic invertebrates EL50, 48 hours: 10.4 mg/l, Daphnia magna Acute toxicity - Microorganisms EC50, 3 hours: 1000 mg/l, Activated sludge
12.2 Persistence & degradability	ΝΟ ΦΑΤΑ
12.3 BIO- ACCUMULATIVE POTENTIAL	PARTITION COEFFICIENT LOG POW: 6.995
12.4 Mobility in soil	NO ADDITIONAL DATA AVAILABLE.
12.5 RESULTS OF PBT & VPVB ASSESSMENT	NO ADDIITIONAL DATA AVAILABLE.
12.6 ENDOCRINE DISRUPTING PROPERTIES	NO ADDITIONAL DATA AVAILABLE.
12.7 Other adverse effects	NO ADDITIONAL DATA AVAILABLE.
SECTION 13: DISPOSAL INFORMATION	
13.1 Waste treatment methods	DO NOT ALLOW ENTRY INTO DRAINS OR WATERWAYS. WASTE: WASTE MANAGEMENT IS CARRIED OUT WITHOUT ENDANGERING HUMAN HEALTH, WITHOUT HARMING THE ENVIRONMENT AND, IN PARTICULAR WITHOUT RISK TO WATER, AIR, SOIL, PLANTS OR ANIMALS. RECYCLE OR DISPOSE OF WASTE IN COMPLIANCE WITH CURRENT LEGISLATION, PREFERABLY VIA A CERTIFIED COLLECTOR OR COMPANY. DO NOT CONTAMINATE THE GROUND OR WATER WITH WASTE. DO NOT DISPOSE OF WASTE INTO THE ENVIRONMENT. SOILED PACKAGING: EMPTY CONTAINER COMPLETELY. KEEP LABEL(S) ON CONTAINER. DISPOSE OF VIA A CERTIFIED DISPOSAL CONTRACTOR.

SECTION 14: TRANSPORT INFORMATION	
14.1 Transport Information	
	ROAD: 3082
UN NUMBER	RAIL: 3082
	AIR: 3082
14.2 UN Shipping Name	ENVIRONMENTALLY HAZARD SUBSTANCE LIQUID, N.O.S
14.3 Transport hazard class(es)	ADR/RID ADR/RID – Class 9 ADR Classification Code – M6 ADR transport category - 3 Hard identification number - 90 Special provisions – 274 335 375 601 Limited quantities – 5L





	EXPECTED QUANTIFIES – E1 Emergency Action Code – •3Z
	IMDG IMDG – Class 9 Special Provisions – 274 335 375 601 Limited quantities – 5L Expected quantities – E1 IMDG EMS – F-A, S-F Stowage and Handling – Category A
	ICAO/IATA ICAO/IATA- CLASS 9 IATA PROPER SHIPPING NAME - ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID N.O.S. EXPECTED QUANTITIES – E1 TRANSPORT LABEL:
14.4 Packing Group	ADR/RID PACKING GROUP: III IMDG PACKING GROUP: III ICAO PACKING GROUP: III
14.5 Enviromental Hazards	ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT.
14.6 Special precautions for user	See sections 6 - 8.
14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL73/78 & THE IBC CODE.	NOT APPLICABLE.
SECTION 15: REGULATORY INFORMATION	
15.1	
PRODUCT SPECIFIC SAFETY, HEALTH & ENVIRONMENTAL REGULATIONS & LEGISLATION	
EU DIRECTIVES	REGULATION (EC) NO 2020/878 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 18 TH DECEMBER 2006. CONCERNING THE REGISTRATION, EVALUATION, AUTHORIZATION & RESTRICTION OF CHEMICALS (REACH), ESTABLISHING A EUROPEAN CHEMICALS AGENCY, AMENDING DIRECTIVE 1999/45/EC and REPEALING COUNCIL REGULATION (EEC) NO793/93 & COMMISSION REGULATION (EC) NO1488/94 AS WELL AS COUNCIL DIRECTIVE 76/769/EEC & COMMISSION DIRECTIVE 91/155/ECC, 93/67/ECC, 93/105/EEC & 2000/21/EC (INCLUDING AMENDMENTS).
STATUTORY INSTRUMENTS	THE CHEMICALS (HAZARD INFORMATION & PACKAGING FOR SUPPLY REGULATIONS 2009 (S.I.2009
Approved Code of Practice	NO 716). Classification & labelling of substances & preparations dangerous for supply. Safety data sheets for substances & preparations.
Guidance Notes	WORKPLACE EXPOSURE LIMITS EH40. CHIP FOR EVERYONE HSG 108.
15.2 Chemical Safety Assessment	-

SECTION 16: OTHER INFORMATION

with O&3 regularly. The information is not and should not be considered a guarantee or warranty, or a part of our contractual or other legal obligations. The information is not to be disclosed to others, reproduced or transmitted in whole or in part without permission from O&3.





Hazard and/ or Precautionary Statements in full	H226 FLAMMABLE LIQUID AND VAPOUR. H302 HARMFUL IF SWALLOWED. H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. H312 HARMFUL IN CONTACT WITH SKIN. H315 CAUSES SKINI IRRITATION. H317 MAY CAUSE AN ALLERGIC SKIN REACTION. H318 CAUSES SERIOUS EYE DAMAGE. H319 CAUSES SERIOUS EYE IRRITATION. H361 SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. H400 VERY TOXIC TO AQUATIC LIFE. H411 TOXIC TO AQUATIC LIFE. H412 HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.
TRAINING INSTRUCTIONS: REFER TO POSSIBLE HAZARD BEFORE USE OF THIS PRODUCT.	
Abbreviations & Acronyms:	
MSDS	MATERIAL SAFETY DATA SHEET.
INCI	INTERNATIONAL NOMENCLATURE OF COSMETIC INGREDIENTS.
CAS	CHEMICAL ABSTRACT SERVICE.
IMDG	INTERNATIONAL MARITIME CODE FOR DANGEROUS GOODS.
ADR	ACCORD EUROPEAN SUR LE TRANSPORT DES MERCHANDISES DANGEREUSES PAR ROUTE (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD).
RID	International Carriage of Dangerous Goods by Rail.
ICAO	INTERNATIONAL CIVIL AVIATION ORGANIZATION.
ADN	International Carriage of Dangerous Goods by Inland Waterways.
GHS	GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION & LABELLING OF CHEMICALS.
TREM CARD	TRANSPORT EMERGENCY CARD.
STOT	SPECIFIC TARGET ORGAN TOXICITY.

DATE	CHANGE DESCRIPTION
10 [™] April 2018	Data Launch
OCOTBER 2020	Review
2021	Review
DECEMBER 2022	EU REGULATION CHANGED

